## Approved For Release 2003/06/24 : CIA-RDP79-01578A000200090003-7

18 December 1974

TATINTMEMORANDUM	FOR:	
------------------	------	--

FROM

OJCS/AD

SUBJECT

: OCR Specifications

PROJECT

RECSKD (22400 AW)

The following items will be needed:

1. OCR type element #915 OCRA

Regular bond paper with no water marks (xerox copy paper works fine)

The following are OCR typing restrictions:

- 1. A one inch margin on top, bottom, and sides must be maintained.
- 2. Double spacing on all pages.
- 3. Each field of data is to be typed on a new line.
- 4. Each line of data has the | symbol as a last character of the field.
- 5. After the last line of data is typed on the page, double space and type the A symbol in the first position of the new line.
- 6. Corrections will be done as follows:
  - a. Character deletion either the  $\mbox{\tt \#}$  or the  $\mbox{\tt $\downarrow$}$  symbols can be used. For example

FREEJD

would be read as FRED

Note: Only the  $\downarrow$  can delete the character | used to end a line.

b. Line deletion - either a line drawn thru the data with a black ink pen or the symbol 1 can be used. It is recommended that the 1 method be used. The typist simply types a 1 at the end of a line of data not desired, double spaces, and retypes the line correctly.

## Approved For Release 2003/06/24 : CIA-RDP79-01578A000200090003-7

- 7. End of page is indicated by a A symbol. This symbol will be on its own line, a double space after the last line of data on the page.
- 8. A cover sheet is required for each batch of input pages. The first line, first position should have the sumbols Al. The second line, first position should have the sumbol A.

## STATINTL

9. The paper is to be typed along the long edge.

If there is any questions about the above instructions, please call

Attached is a sample of the cover sheet and one page of data.